



Consume

Grease & Scum Digestor

Consume removes scum cake and grease in water treatment plants and sewers.

DIRECTIONS FOR USE

OVERALL PLANT TREATMENT: Use **Consume** to prevent grease build up after scum blanket is eliminated. Allow one gallon **Consume** to drip into influent every 24 hours (45 drops per minute) (1/4 to 1/2 ppm)

PUMPING STATIONS, WET WALLS, & SEWER LINES: Add **Consume** directly Into force mains, wet walls, pumping stations, and sewer lines as needed to remove build up. Not affected by temperature - use even in below zero weather.

ELIMINATING SCUM CAKE & GREASE: Through any port or inspection hole, add 20 to 25 gallons of **Consume** followed immediately by the addition of 500 - 2,000 gallons of water. Wet down top of grease cake with water daily. Daily addition of 1 to 2 gallons of **Consume** in the sludge compartment allows effective and continuous treatment of both top and bottom of grease cake. Circulation should be continued as usual.

STUCK FLOATING DIGESTOR COVERS: Apply **Consume** around edge of cover and wet with hose.

TECHNICAL DATA

Color.....	Clear
Scent.....	Chemical
Foaming	Medium
Solubility in Water	Complete
Density (lb/gal)	8.8
Flash Point	N/A
pH	13.8





FEATURES & BENEFITS



PO Box 1990 | Largo, FL 33779

©Copyright 2007 Gator Chemical Company. All rights reserved.
Gator Chemical Company manufactures...