



Easy Coat 20

Sealer/Finish

Easy Coat 20 is a metal interlock sealer/finish that provides excellent durability, high initial gloss, and wet look response to ultra high-speed maintenance. UL Classified.

DIRECTIONS FOR USE

APPLICATION: Remove all dirt and old finish by using a floor machine and **Easy Strip**, **Speedy Strip**, or **Enviro Strip**. Rinse floor thoroughly and allow to dry. Apply **Easy Coat 20** in medium to heavy, uniform coats with a finish mop. Let dry thoroughly (45 minutes) before applying a second coat. Usually, no more than four (4) coats are necessary. Do not pour unused product back into container.

MAINTENANCE: Dust mop, damp mop, or sweep as necessary. **Easy Coat 20** can be buffed as soon as it is dries. However, for best results, allow to cure 24 hours before ultra high speed buffing. Dry buff as necessary, using propane, battery, or other ultra high speed buffing equipment. Buff only with ultra high speed buffing pads. Maintain/repair traffic areas with finish applications as necessary following appropriate surface preparation, i.e., buffing, dust mopping, top scrubbing with **Neutra Clean**. Use **Restore** for quick repair of traffic areas.

TECHNICAL DATA

Color.....	White Emulsion
Scent.....	Acrylic
Foaming.....	N/A
Solubility in Water	Complete
Density (lb/gal)	8.65
Flash Point	None
pH	8.5





FEATURES & BENEFITS

Easy Coat 20

Sealer/Finish

FEATURES

- Metal interlock
- Sealer/Finish combination
20% solids
- Easy to use
- Self-leveling
- Fast drying time; non-yellowing
- Non-powdering
- Slip-resistant (UL approved)
- Black mark/scuff resistant
- Versatile
- Reduces labor / looks great

CUSTOMER BENEFITS

- Detergent resistant
- Limits inventory
- Reduces training time
- Dries without streaking
- Recoat sooner; less down;
prolongs stripping
- Film stays intact
- Less worry / less buffing time
- Acceptable with any speed
equipment (175 to 3200 rpm)
- Saves dollars
- Promotes employee moral and
high public opinion

