



Enviro Strip

Non-Butyl Floor Stripper

Enviro Strip is a powerful stripper designed for removing both floor finish and sealers.

DIRECTIONS FOR USE

REMOVING FLOOR FINISH: Use 12 ounces of **Enviro Strip** per gallon of water. Wet floor. Allow to stand 10 minutes. Do not allow **Enviro Strip** to dry on floor. Machine scrub. Pick up solution with a mop or a wet/dry vacuum. Rinse floor at least twice with clean, cold water. After floor is dry, apply finish.

REMOVING FINISH AND SEALER: Use 32 ounces of **Enviro Strip** per gallon of water. Wet floor. Allow to stand 15 minutes. Do not allow **Enviro Strip** to dry on floor. Machine scrub. Pick up solution with a mop or a wet/dry vacuum. Rinse floor at least twice with clean, cold water. After floor is dry, apply finish.

TECHNICAL DATA

Color.....	Red
Scent.....	Chemical
Foaming.....	Low
Solubility in Water	Complete
Density (lb/gal)	8.6-8.75
Flash Point.....	None
pH	13.2





Enviro Strip

Non-Butyl Floor Stripper

FEATURES

Contains no butyl

Safer for workers

Versatile

Economical

Labor saver

Pleasant fragrance

CUSTOMER BENEFITS

Eliminates noxious vapors; no headaches

Not under SARA Title III, Section 313; NIOSH standard

Strips polymer floor finishes, acrylic seals, water-based urethanes

Dilutes at 1-10, 1-4 for removing acrylic seals

Strips first time

A pleasure, workers love it

FEATURES & BENEFITS



PO Box 1990 | Largo, FL 33779

©Copyright 2007 Gator Chemical Company. All rights reserved.
Gator Chemical Company manufactures...